

# SPP-R310

3 inch Mobile Printer



# Compact and Ergonomic



Compatible with



Made for iPod iPhone iPad



### Smaller and Lighter Design

- Easy to grip: 30% lighter and 26% slimmer than SPP-R300
- One touch cover open and easy paper loading



SPP-R300

SPP-R310

Made for iPod iPhone iPad



### Mobile Field-Work Optimization

- Wireless and wired connectivity options including Bluetooth, WiFi, USB and Serial
- Supporting Easy Bluetooth Pairing™ via embedded NFC tag enabling auto pairing
- Apple® MFi certified model (Auto-switchable from iOS mode to standard Bluetooth mode)
- IP43 (Printer only) / IP54 (with protective case)
- 1.8 m / 6 ft. drop rate
- Long-lasting battery life (24-hour stand by time)



### Built for Multi-Purpose

- Fast printing speed up to 100 mm/sec (Receipt)
- Designed for the receipt and label printing (Simple to switch via the feed button)
- Optional linerless label printing (80 mm/sec at 203dpi)

**BIXOLON®**  
a Better Solution for your Business™

# SPP-R310

## 3 inch Mobile Printer



Reported by Chunichisha

## Specifications

### Printer Specifications

**Print Method**  
Direct Thermal

**Print Speed**  
Up to 100 mm/sec (Receipt)  
Up to 80 mm/sec (Linerless)  
12.5% pattern

**Print Resolution**  
203 dpi

**Print Width**  
Up to 72 mm

**Sensor**  
Paper End: Reflective sensor  
Paper Cover Open: Mechanical switch

### Media Characteristics

**Media Type**  
Receipt, Label and Linerless (Optional)

**Media Width**  
80 mm

**Media Roll Diameter**  
Up to 50 mm

**Media Thickness**  
0.07 ± 0.005 mm

**Supply Method**  
Easy paper loading

### Physical Characteristics

**Dimensions (WxLxD)**  
105.0 x 126.0 x 58.0 mm  
(4.14 x 4.97 x 2.29 inch)

**Weight**  
Including battery: 385 g (0.85 lbs.)  
Including MSR: 405 g (0.9 lbs.)  
Paper: 133 g (0.29 lbs.)

**Battery**  
7.4 V Li-ion, 2,600 mAh, Rechargeable  
Charging time: Up to 4.0 hrs

### Performance Characteristics

**Memory**  
64 Mbit SDRAM, 32 Mbit FlashROM

**Interface Options**  
Standard: USB V2.0 FS + Serial  
Optional: USB V2.0 FS + Serial + Bluetooth  
V3.0 + EDR\* / WLAN 802.11b/g/n  
(Infrastructure, Ad-hoc, Wi-Fi Direct) -  
WEP40/104, WPA1/2(PSK, EAP)  
\* Easy Bluetooth Pairing™ via NFC

### Environment Characteristics

**Temperature**  
Operating: -15 ~ 50°C (5 ~ 122°F)  
Storage: -30 ~ 70°C (-22 ~ 158°F)

**Humidity**  
Operating: 10 ~ 80% RH

**Sealing**  
IP43 (IP54 with protective case)

**Drop Rate**  
1.8 m (6 ft.)

### Software

**Emulation**  
BXL / POS

**Drivers**  
Windows Driver, OPOS Driver, JPOS Driver,  
Linux CUPS Driver

**SDKs**  
iOS SDK, Android SDK, Windows SDK

### Fonts / Graphics / Symbologies

**Character Size**  
Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24  
KOR, CHN: 24 x 24

**Characters Per Line**  
Font A: 48 Font B, C: 64  
KOR, CHN: 24

**Character Sets**  
Alphanumeric: 95  
Expanded Graphics: 128 x 33 page  
International: 32

**Graphics**  
Supporting user-defined fonts, graphics,  
formats, layouts, and logos

**Barcode**  
1D: Codabar, Code 39, Code 93, Code 128, EAN-8,  
EAN-13, ITF, UPC-A, UPC-E  
2D: Aztec, Data Matrix, GS1 Databar, MaxiCode,  
PDF417, QR code

### Accessories

**Standard**  
Belt Clip, Battery Pack, Battery Charger,  
Power Cord, Paper

**Optional**  
Belt Strap, Case, Protective Case, Shoulder Strap,  
Single Battery Cradle, Quad Battery Charger,  
Cigarette Lighter Charger, Serial/USB Cable,  
Cleaning Pen

### Integrated Card Reader (Optional)

**MSR**  
3 Track (T-DES/DUKPT(Optional))

