



SEAMLESS MOBILITY WITH EXCEPTIONAL PERFORMANCE

3 inch POS Printer **SRP-350plusII**



HIGHLIGHTS



High-quality Printing Performance

- Fast printing up to 300mm/sec (20% faster than the SRP-350plusII)
- Cost-saving paper reduction function (Barcode reduction included)
- 16-step true gray scale printing of graphics
- Proven-reliability as a family of steady-selling SRP-350 line



World-class Flexibility

- Compatible with smart device including iOS (MFi optional), Android, and Windows RT 8.1
- Simple-to-use Wifi or Bluetooth wireless printing (optional)
- Built-in USB and Ethernet

User-friendly Design

- Anti-jam guide
- Stand-alone or Space-saving wall-mount use
- 2" or 3" paper choice



BIXOLON[®]
a Better Solution for your Business[™]

3 inch POS Printer SRP-350plusIII



SPECIFICATIONS

Print Characteristics

Print Method

Direct Thermal

Print Speed

SRP-350plusIII: 300 mm/sec

SRP-352plusIII: 270 mm/sec

Print Resolution

SRP-350plusIII: 180 dpi

SRP-352plusIII: 203 dpi

Print Width

Up to 72 mm

Sensor

Paper End, Paper Near End, Cover Open

Media Characteristics

Media Type

Receipt

Media Width

80 mm / 58 mm

Media Roll Diameter

Up to 83 mm

Media Thickness

0.062 ~ 0.075 mm

Supply Method

Easy Paper Loading

Physical Characteristics

Dimensions (WxLxD)

145 x 200 x 146 mm

(5.70 x 7.87 x 5.74 inch)

Weight

1.56 kg (3.43 lbs)

Power

EnergyStar Certified,

External Power Adaptor 100-240V AV, 50/60Hz

Drawer Port

2 ports (via y-type adaptor)

Performance Characteristics

Memory

64 Mbit SDRAM, 32 Mbit FlashROM

NV Image Memory

768 Kbytes (mono)

Receive Buffer

4 Kbytes

User Define Buffer

12 Kbytes

Interface

Triple Interface

USB V2.0 FS + Ethernet + Serial / Parallel /

WLAN* / Bluetooth V2.1+ EDR** / powered USB

* WLAN: 802.11b/g/n

**Bluetooth: Class 1 (100 m), MFi certified

Environment Characteristics

Temperature

Operating: 0 ~ 45°C (32 ~ 113°F)

Storage: -20 ~ 60°C (-4 ~ 140°F)

Humidity

Operating: 10 ~ 80% RH

Storage: 10 ~ 90% RH

Reliability

Printer Unit (MCBF)

70 Million Lines

Thermal Print Head (TPH)

150 km

Auto Cutter

1.8 Million Cuts

Software

Emulation

BXL / POS

Driver / Utility

Windows Driver, OPOS Driver, JPOS Driver,

Linux CUPS Driver, Mac Driver,

Virtual COM USB/Ethernet Driver, Utility Program

SDK

iOS SDK, Android SDK, Windows SDK

Fonts / Graphics / Symbologies

Character Size

Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24

KOR, CHN, JPN: 24 x 24

Characters Per Line

SRP-350plusIII: Font A: 42 Font B, C: 56

KOR, CHN, JPN: 21

SRP-352plusIII: Font A: 48 Font B, C: 64

KOR, CHN, JPN: 24

Character Sets

Alphanumeric: 95

Extended Graphics: 128 x 37 page

International: 32

Graphics

Supporting user-defined fonts, graphics, formats, and logos

Barcode Symbologies

1D: Codabar, Code 39, Code 93, Code 128,
EAN-8, EAN-13, ITF, UPC-A, UPC-E

2D: Data Matrix, PDF417, QR code

BR-SRP-350plusIII-EN-APR14-V1

Copyright © BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

BIXOLON®

www.bixolon.com

**BIXOLON Co., Ltd.**

7~8F, (Sampyeong-dong), 20, Pangyoyeok-ro241beon-gil,
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, Korea (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

BIXOLON America Inc.

3171 Fujita St Torrance,
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

BIXOLON Europe GmbH

Tiefenbroicher Weg 35,
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de