



# **BIXOLON** Certified Linerless Media

- The following media is compatible with BIXOLON Printers
- Using non-compatible media may cause technical issues which are not covered by warranty or service agreements



## ICONEX

Media Type	Classic						Classic High Tack			Classic High Temp			Ultralite			Classic High Tack Plus		Linerless Extreme (Snag Resistant)		Linerless Extreme (Freshness Labeling)			High-Temp Hi-Tack		
Product Line	9023-1253	9023-1232	9023-1823	9023-1397	9023-1233	9023-1818	9023-1254	9023-1500	9023-1258	9023-1267	9023-1463	9023-1269	9023-1866	9023-1410	9023-1865	9023-1846		9023-1873	9023-1708	9016-3227	9016-3777	9016-3257	9023-2083		
Dimensions of the Product	Width (mm)		80		58		40		80	58	40	80	58	40	80	58	40	40		40			58		
	Roll Diameter (inch)		4						4			4			4			4		4			4		
	Length (feet)		270						270			270			375			270		270			225		270
Number of Rolls in Carton	12	30	12	30	12	30	12			12	30	12	30			12		12	30	12			12		
Paper Weight (gsm)	80						80			80			55			80		80			80		80		
Recommended Speed	170 mm/s												100 mm/s										150 mm/s		
Supporting High Temp	60°F ~ 120°F (15.5°C ~ 48.9°C)						60°F ~ 120°F (15.5°C ~ 48.9°C)			60°F ~ 120°F (15.5°C ~ 48.9°C)			60°F ~ 120°F (15.5°C ~ 48.9°C)			60°F ~ 120°F (15.5°C ~ 48.9°C)		60°F ~ 120°F (15.5°C ~ 48.9°C)		0°F ~ 212°F (-17.8°C ~ 100°C)			60°F ~ 120°F (15.5°C ~ 48.9°C)		
Applicable Models	SRP-S300						SRP-S300			SRP-S300			SRP-S300			SRP-S300		SRP-S300			SRP-S300		SRP-S300		

Media Type	Center Adhesive				Side-Edge Adhesive								Three and Four Stripe Adhesive		Diamond Adhesive Formation				Full Adhesive		Full Adhesive	
Product Line	Premium		2GO		Premium		2GO		Colors	Spectrum	2GO		PLUSD				X2		X2			
PID	MS 214150	MS 318150	MS 2141602GO	MS 3181602GO	MS 214150SE	MS 318150SE	MS 214782GOSE	MS 3181602GOSE	MS 173223752GO2SHR	MS 3181602GOSE (B,G,C,P,O,Y*)	MS 3181602GOSESP	MS 2142402GO3S	MS 3182402GO4S	MS 1732290PLUSD HVHR	MS 214290PLUSD	MS 318170PLUSD	MS 3183752GOPLUSD	MS 11732270X2HRHT	MS 214290X2	MS214125X2	MS318125X2	
Dimensions of the Product	Width (mm)		57	80	57	80	57	80	57	80	80	57	80	40	57	80	80	40	58	58	80	
	Roll Diameter (inch)		3		2.8		3	3	2	2.8	4	2.8	2.8	3.2	3.2	4	4	3.2	4	4	4	2.6
Length (feet)		150	150	160	160	150	150	78	160	375	160	160	240	240	290	290	170	375	300	290	125	125
Number of Rolls in Carton	24	24	24	24	24	24	72	24	12	24	28	32	32	12	32	32	12	12	12	50	50	
Paper Weight (gsm)	80	80	55	55	80	80	55	55	64	55	55	55	55	64	80	80	55	64	80	74	74	
Recommended Speed	150 mm/s				150 mm/s				100 mm/s	150 mm/s			150 mm/s		100 mm/s	150 mm/s		100 mm/s	100 mm/s	170 mm/s	127 mm/s	127 mm/s
Applicable Models	SRP-S300				SRP-S300								SRP-S300		SRP-S300				SRP-S300		XM7-30, SPP-L3000	

\*Available Colors: Blue, Green, Canary, Pink, Orange and Violet



## StickyPOS

Product Line		BT		ECO BT		2CR-11		ECO 2CR-11	40M R	ECO BT	FCE 2HT		PBE 2HT
PID		BT 80X350	BT 58X350	ECO BT 80X315	ECO BT 58X315	2CR-11 80X350	2CR-11 58X350	ECO 2CR-11 80X315	40MM R L90-9000	ECO BT 40X315	FCE 2HT 80X250	FEC 2HT 58X250	PBE 2HT 40X250
Dimensions of the Product	Width (mm)	80	58	80	58	80	58	80	40	40	80	58	40
	Roll Diameter (inch)	4		4		4		4	4	4	4	4	4
	Length (feet)	350	150	315	315	350	350	315	350	315	250	250	250
Number of Rolls in Carton		18 or 30	18 or 27	18 or 30	18 or 27	18 or 30	18 or 27	18 or 30	18 or 36	18 or 36	18 or 30	18 or 27	18 or 36
Paper Weight (gsm)		55	55	55	55	55	55	55	55	55	74	74	74
Recommended Speed		150 mm/s		100 mm/s		150 mm/s		130 mm/s	150 mm/s	100 mm/s	130 mm/s		
Supporting High Temp		N/A		N/A		N/A		N/A		Supporting			
Applicable Models		SRP-S300		SRP-S300		SRP-S300		SRP-S300		SRP-S300			

## Blumberg

Media Type		Permanent Adhesive				
Product Line		Linerless Externe				
PID		A11649	A12978	A10944	A14373	A12932
Dimensions of the Product	Width (mm)	58	80	58	80	112
	Roll Diameter (inch)	4	4	4	4	2.2
	Length (feet)	260	262	328	328	78
Number of Rolls in Carton		-	5	18	18	30
Paper Weight (gsm)		88.0 +/- 8.0	80	93 +/- 10	93 +/- 10	77
Recommended Speed		100 mm/s	100 mm/s	100 mm/s	100 mm/s	60 mm/s
Applicable Models		SRP-S300		SRP-S320		SPP-R410

## Dykam

Media Type		Permanent Adhesive	
Product Line		Linerless Externe	
PID		4030115	
Dimensions of the Product	Width (mm)	100	
	Roll Diameter (inch)	4.9 +/- 0.05	
	Length (feet)	394	
Number of Rolls in Carton		4	
Paper Weight (gsm)		72 +/- 10	
Recommended Speed		127 mm/s	
Applicable Models		XL5-40	

## BIZERBA

Media Type		Full Adhesive		
Product Line		Linerless Top	Eco BK 002C	Linerless Premium Top
PID		402 00000 00209	402 00000 00206	402 00000 00085
Dimensions of the Product	Width (mm)	58	58	58
	Roll Diameter (inch)	4	4	4
	Length (feet)	262	262	262
Number of Rolls in Carton		30	30	30
Paper Weight (gsm)		73	71	80
Recommended Speed		150 mm/s		
Applicable Models		SRP-S300/S320		

## NAStar

Media Type		Full Adhesive	
Product Line		NAStar Print'N Stick Eco	NAStar Print'N Stick Plus
PID		SWDTXM1 3.125.155	SWDTXS 3.125.155
Dimensions of the Product	Width (mm)	79.4	79.4
	Roll Diameter (inch)	3	3
	Length (feet)	155	155
Number of Rolls in Carton		48	48
Paper Weight (gsm)		73	75
Recommended Speed		100 mm/s	130 mm/s
Applicable Models		SRP-S300	

## Sato

Media Type		Peelable Adhesive	Permanent Adhesive	
Product Line		Re-stick	Linerless Externe	
PID		585006411	585006451	Y58129231338
Dimensions of the Product	Width (mm)	79.5	79.5	80
	Roll Diameter (inch)	4	4	4
	Length (feet)	240	240	354
Number of Rolls in Carton		100	100	12
Paper Weight (gsm)		90.8 +/- 10.1	89.7 +/- 8.1	80.0 +/- 10.0
Recommended Speed		170 mm/s	100 mm/s	150 mm/s
Applicable Models		SRP-S300		

## UPM Raflatac

Media Type		Removable	
Product Line		THERMAL LINERLESS TPFREE CO2N-FSC/ RL50 OPTICUT	
PID		FWK/RL50/00/E0	
Dimensions of the Product	Width (mm)	80	
	Roll Diameter (inch)	4	
	Length (feet)	260	
Number of Rolls in Carton		18	
Paper Weight (gsm)		75	
Recommended Speed		100 mm/s	
Applicable Models		SRP-S300J	

# BIXOLON Certified Linerless Media



BR\_BIXOLON Certified Linerless Media\_EN\_DEC23\_V1

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

**BIXOLON**

[www.BIXOLON.com](http://www.BIXOLON.com)

**BIXOLON Co.,Ltd.**  
+82 31 218 5500  
[sales@bixonon.com](mailto:sales@bixonon.com)

**BIXOLON America Inc.**  
+1 858 764 4580  
[sales@bixononusa.com](mailto:sales@bixononusa.com)

**BIXOLON Mexico**  
+521 55 8852 7880  
[marcelo@bixononusa.com](mailto:marcelo@bixononusa.com)

**BIXOLON Europe GmbH**  
+49 211 68 78 54 0  
[sales@bixonon.de](mailto:sales@bixonon.de)

**BIXOLON MEA**  
+971 4 222 6480  
[russell@bixonon.com](mailto:russell@bixonon.com)