



유통



병원·약국



우편·택배



참고관리

# SLP-TX220

2인치 열전사방식  
데스크탑 라벨 프린터

# Premium, Compact, and High Performance



6  
IPS

### 프리미엄급 제품 설계

- 주요 프로그래밍 언어와의 높은 호환성
- 최고 6ips (152 mm/sec)의 인쇄 속도
- 대용량 메모리 탑재로 빠른 데이터 처리 (64MB SDRAM, 128MB Flash Rom)
- Smart Media Detection™  
: 용지 타입 및 라벨 길이 자동 인지

Made for  
iPhone iPad



### 모바일 환경의 최적화

- 세계 최초 내장형 블루투스 탑재 (MFi iAP2인증)
- 스마트 블루투스 자동 변경 (iOS ↔ Standard 블루투스)
- 안드로이드, iOS, 윈도우 등 모바일 운영체제와의 호환



Peeler



Auto-cutter

### 사용자 중심의 디자인

- 74 mm 리본사이즈로 최적화 된 디자인
- 다양한 옵션 제공 : 필러, 자동 커터 등
- 리본과 용지 장착이 간편
- 용지 센서 (Gap, Black Mark)
- 손쉬운 용지 교체
- 편리한 정지 / 취소 버튼



# SLP-TX220

2인치 열전사방식  
데스크탑 라벨 프린터

## Specifications

### Printer Specifications

#### Print Method

Thermal Transfer, Direct Thermal

#### Print Speed

SLP-TX220: Up to 6 ips (152 mm/sec)  
SLP-TX223: Up to 4 ips (100 mm/sec)

#### Print Resolution

SLP-TX220: 203 dpi  
SLP-TX223: 300 dpi

#### Print Width

SLP-TX220: Up to 54 mm  
SLP-TX223: Up to 56.9 mm

#### Print Length

6 ~ 2000 mm

#### Sensor

Transmissive, Reflective (Adjustable),  
Head open

### Media Characteristics

#### Media Type

Gap, Black Mark, Notch, Continuous, Fan-Fold

#### Media Width

15 ~ 60 mm

#### Media Roll Diameter

Up to 130 mm

#### Media Thickness

0.06 ~ 0.20 mm

#### Supply Method

Easy Paper Loading

### Ribbon Characteristics

#### Ribbon Type

Wax, Wax/Resin, Resin, Outside

#### Ribbon Width

58 mm

#### Ribbon Length

Up to 74 m

#### Ribbon Width

12.5 mm

### Physical Characteristics

#### Dimensions (WxDxH)

144 x 250 x 173mm  
(5.67 x 9.84 x 6.81 inch)

#### Weight

1.71 kg (3.77 lbs.)

#### Power

EnergyStar Certified,  
External Power Adaptor 100-240V AC, 50/60Hz

### Performance Characteristics

#### Memory

64MB SDRAM, 128MB FlashROM

#### Interface Options

Standard: USB+Serial+Parallel  
Optional: ① USB+Serial+Ethernet+WLAN\*  
② USB+WLAN\*+Bluetooth\*\*

\* WLAN: 802.11b/g/n USB dongle type (optional)

\*\* Bluetooth: Built-in type, MFi iAP2 certified

### Environment Characteristics

#### Temperature

Operating: 5 ~ 40°C (41 ~ 104°F)  
Storage: -20 ~ 60°C (-4 ~ 140°F)

#### Humidity

Operating: 10 ~ 80% RH  
Storage: 10 ~ 90% RH

### Software

#### Emulation

SLCS, BPL-Z™, BPL-E™

#### Drivers

Windows Driver (Euro Plus/Seagull),  
Linux / Mac CUPS Driver,  
Virtual COM USB/Ethernet Driver,  
Utility Program, Label Artist™

#### SDKs

Android SDK, iOS SDK, Windows SDK

### Fonts / Graphics / Symbologies

### Fonts

- 10 SLCS Resident Bitmap Fonts
- One SLCS Resident Scalable Font
- 16 BPL-Z™ Resident Bitmap Fonts
- One BPL-Z™ Resident Scalable Font
- 5 BPL-E™ Resident Bitmap Fonts
- 23 Code Page
- Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

### Graphics

Supporting user-defined fonts, graphics,  
formats, and logos

### Barcode Symbologies

- 1D: Codabar, Code 11, Code 39, Code 93,  
Code 128, EAN-13, EAN-8, Industrial 2-of-5,  
Interleaved 2-of-5, Logmars, MSI, Plessey,  
Postnet, GS1 DataBar (RSS-14), Standard  
2-of-5, UPC/EAN extensions, UPC-A, UPC-E,  
IMB
- 2D: Aztec, Codablock, Code49, Data Matrix,  
MaxiCode, MicroPDF417, PDF417,  
QR Code, TLC39

### Options

Ethernet, WLAN (USB dongle type), Peeler,  
Auto Cutter, RTC (Real Time Clock),  
Bluetooth(Built-in type), External Paper Supply

