

# SLP-DL410

4인치 감열식  
초소형 데스크탑 라벨 프린터



# Ultra-Compact and Specialized



### 초소형 디자인과 다양한 옵션

- 표준 : Fan-fold type (접이식)
- 옵션 :
  - 외장형 용지 공급 (최대 Ø150 mm or 205 mm)
  - 외장형 파워 아답터
  - Peeler or Auto-Cutter



세계에서 가장 작은 사이즈

5  
IPS



### 프리미엄급 제품 설계

- 주요 프로그래밍 언어와의 높은 호환성
- 최고 5ips (127 mm/sec)의 인쇄 속도
- 대용량 메모리 탑재로 빠른 데이터 처리 (64MB SDRAM, 128MB Flash Rom)
- Smart Media Detection™: 용지 타입 및 라벨 길이 자동 인지



Short length media label



Gap media label



Black mark media label



Continuous label

Made for iPod iPhone iPad



### 모바일 환경의 최적화

- 세계 최초 내장형 블루투스 탑재 (MFi iAP2인증)
- 스마트 블루투스 자동 변경 (iOS↔표준 블루투스)
- 안드로이드, iOS, 윈도우 등 모바일 운영체제와의 호환

**BIXOLON**  
a Better Solution for your Business™

# SLP-DL410

4인치 감열식  
초소형 데스크탑 라벨 프린터

## Specifications

### Printer Specifications

#### Print Method

Direct Thermal

#### Print Speed

SLP-DL410: Up to 5 ips (127 mm/sec)  
SLP-DL413: Up to 5 ips (127 mm/sec)

#### Print Resolution

SLP-DL410: 203 dpi  
SLP-DL413: 300 dpi

#### Print Width

SLP-DL410: Up to 108 mm  
SLP-DL413: Up to 105.7 mm

#### Print Length

6 ~ 2000 mm

#### Sensor

Transmissive, Reflective (adjustable),  
Head open

### Media Characteristics

#### Media Type

Gap, Black Mark, Notch, Continuous, Fan-Fold

#### Media Width

25 ~ 116 mm

#### Media Roll Diameter

External roll media options up to  
Ø 150 mm to 205 mm

#### Media Thickness

0.06 ~ 0.20 mm

### Physical Characteristics

#### Dimensions (WxDxH)

177 x 150 x 148.5 mm  
(6.97 x 5.91 x 5.85 inch)

#### Weight

1.6 kg (3.53 lbs.)

#### Power

EnergyStar Certified,  
Internal Power Adaptor 100-240V AC, 50/60Hz

### Performance Characteristics

#### Memory

64MB SDRAM, 128MB FlashROM

#### Interface Options

Standard: USB+WLAN\*

Optional: ① USB+Ethernet+WLAN\*

② USB+Ethernet+WLAN\*+Bluetooth\*\*

③ USB+WLAN\*+Bluetooth\*\*

\* WLAN: 802.11b/g/n USB dongle type (optional)

\*\* Bluetooth: Built-in type, MFi iAP2 certified

### Environment Characteristics

#### Temperature

Operating: 0 ~ 40°C (32 ~ 104°F)

Storage: -20 ~ 60°C (-4 ~ 140°F)

#### Humidity

Operating: 10 ~ 80% RH

Storage: 10 ~ 90% RH

### Software

#### Emulation

SLCS, BPL-Z™, BPL-E™

#### Drivers

Windows Driver (Euro Plus/Seagull),

Linux / Mac CUPS Driver,

Virtual COM USB/Ethernet Driver,

Utility Program, Label Artist™

#### SDKs

Android SDK, iOS SDK, Windows SDK

### Fonts / Graphics / Symbologies

#### Fonts

- 10 SLCS Resident Bitmap Fonts
- One SLCS Resident Scalable Font
- 16 BPL-Z™ Resident Bitmap Fonts
- One BPL-Z™ Resident Scalable Font
- 5 BPL-E™ Resident Bitmap Fonts
- 23 Code Page
- Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

#### Graphics

Supporting user-defined fonts, graphics,  
formats, and logos

#### Barcode Symbologies

1D: Codabar, Code 11, Code 39, Code 93,  
Code 128, EAN-13, EAN-8, Industrial 2-of-5,  
Interleaved 2-of-5, Logmars, MSI, Plessey,  
Postnet, GS1 DataBar (RSS-14), Standard  
2-of-5, UPC/EAN extensions, UPC-A, UPC-E,  
IMB

2D: Aztec, Codablock, Code 49, Data Matrix,  
MaxiCode, MicroPDF417, PDF417,  
QR code, TLC 39

#### Options

Ethernet, WLAN (USB dongle type), Peeler,  
Auto Cutter, RTC (Real Time Clock),  
Bluetooth(Built-in type),  
External Paper Supply, External Power Adaptor

