

# SRP-350plusV

3-inch Thermal POS Printer



## Spec Sheet

### Print Characteristics

#### Print Method

Direct Thermal

#### Print Speed

SRP-350plusV: Up to 400 mm/sec

SRP-352plusV: Up to 370 mm/sec

#### Print Resolution

SRP-350plusV: 180 dpi

SRP-352plusV: 203 dpi

#### Print Width

Up to 72 mm

#### Sensor

Paper End, Paper Near End, Cover Open, Visibility Intelligence Sensor

### Media Characteristics

#### Media Type

Receipt

#### Media Width

80 mm

Optional 58 mm

#### Media Roll Diameter

Up to 83 mm

#### Media Thickness

0.05 to 0.08 mm

#### Supply Method

Easy Paper Loading

### Physical Characteristics

#### Dimensions (W x L x H)

145 x 200 x 146 mm (5.70 x 7.87 x 5.74 inch)

#### Weight

1.6 kg (3.52 lbs.)

#### Electrical

EnergyStar® Certified,  
External Power Adapter 100-240 V AC,  
50/60 Hz

#### Drawer Port

2 ports (Via Y-Type Adapter)

### Performance Characteristics

#### Memory

64 MB SDRAM, 64 MB Flash

#### NV Image Memory

768 Kbytes (Mono)

#### Receive Buffer

4 Kbytes

#### User Define Buffer

12 Kbytes

#### Interface

Standard: USB 2.0 FS + Ethernet

Optional: ① USB 2.0 FS + Ethernet + Serial

② USB 2.0 FS + Ethernet + Dual Serial

③ USB 2.0 FS + Ethernet + Parallel

④ USB 2.0 FS + Ethernet + WLAN<sup>1</sup>

⑤ USB 2.0 FS + Ethernet + Bluetooth®

⑥ USB 2.0 FS + Ethernet +

Powered USB

WLAN: 802.11a/b/g/n (Infrastructure,  
Ad-hoc, Wi-Fi Direct, SoftAP)–  
WEP40/104, WPA1/2 (PSK, EAP)

### Environment Characteristics

#### Temperature

Operating: 0 to 40°C (32 to 104°F)

Storage: -20 to 60°C (-4 to 140°F)

#### Humidity

Operating: 10 to 80% RH

Storage: 10 to 90% RH

### Software

#### Emulation

BXL/POS™

#### Driver/Utility

Windows® Driver, OPOS/JPOS Driver,  
Linux/Mac® CUPS Driver,  
Virtual COM USB/Ethernet Driver,  
Utility Program, Network Auto Installer

#### Developer Tools

Android™/iOS®/Windows SDK, Linux SDK,  
Xamarin SDK, Web Print SDK, Cordova Plugin,  
MAUI SDK, Flutter™ Plugin, React Native SDK

#### Design & Print

mPrint App (Android, iOS)

#### MDM(Optional)

BIXOLON Profile Manager - XPM™, XCM™  
(Windows, Android)

### Fonts/Graphics/Symbologies

#### Character Size

Font A: 12 x 24, Font B: 9 x 17,

Font C: 9 x 24, KOR, CHN, JPN: 24 x 24

#### Characters per Line

SRP-350plusV: Font A: 42, Font B, C: 56,  
KOR, CHN, JPN: 21

SRP-352plusV: Font A: 48 Font B, C: 64  
KOR, CHN, JPN: 24

#### Character Sets

Alphanumeric: 95

Extended Graphics: 128 x 35 page

International: 32

#### Barcode Symbologies

1D: Coda Bar, Code 39, Code 93,  
Code 128, EAN-8, EAN-13, ITF,  
UPC-A, UPC-E

2D: Data Matrix, PDF417, QR code

### Accessories/Supplies

#### Included in the Box

Paper, AC/DC Adapter, Cable Cover,  
Power Cord, USB A-B Cable 1.8 m,  
DK Gender

#### Options & Accessories

Built-in AC/DC Adapter, Vertical Stand,  
Wall Mount, Splash Proof Cover,  
External Buzzer, B-Melodist,  
Powered USB (0.5/1.2 m),  
Serial Cable (9-9/25-9 pin),  
Powered A-B USB Y Cable (1.2/4.8 m),  
Parallel Cable